





Easy Grinding Close to Walls

IFolding Cover for Working Close to Edges

The folding cover segment, can be opened with a single touch and allows for grinding close to edges.



2 Powerful Motor and Adjustable Speed

The 1,900W powerful motor and adjustable speed settings ensure maximum productivity. The speed is adjustable with a speed adjustment wheel to suit the application and remains almost constant even under load.

3 Durable Safety Guard

The aluminum die-cast guard makes the tool particularly robust.

4 Optimal Dust Extraction

The spring-mounted ring brush provides a high suction effect.

5 Tool-less Adjustable Handle

The ergonomically shaped, tool-less adjustable loop handle supports a comfortable posture while working.

6 Cleaner and Safer Environment

The tool can be connected to HiKOKI dust extractors for a dust-free working environment.



Concrete Grinder

GM 13Y



Specifications

Model		GM 13Y
Max. Diameter of Accessory		125mm
Spindle Thread		M14
Rated Input Power		1,900W (230V)
No Load Speed		3,800 - 8,200/min
Dimensions	Length	475mm
	Width	199mm
	Height	125mm
Weight without Mains Cable*1		3.6kg
Standard Accessories*2		2-hole Spanner, Plastic Case, Diamond Cup Wheel

^{*1.} Weight: According to EPTA-Procedure 01/2003.

Distributed by:

^{*2.} Standard accessories vary by country or area.